



SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION

QUALIFIED PRODUCT POLICY FOR TYPE I(SM) SLAG-MODIFIED PORTLAND
CEMENT

Requests to qualify a product should be directed in writing to:

Aly A. Hussein, PhD, P.E.
Structural Materials Engineer
SCDOT Office of Materials and Research
P.O. Box 191
Columbia, SC 29202
(803) 737-6687
(803) 737-6649 Fax
email: husseinaa@scdot.org

Requests for inclusion should address each of the following requirements.

Requirements for inclusion on the list of qualified suppliers is as follows:

- The supplier must already be qualified to supply both Type I Portland Cement and Granulated Blast Furnace Slag and all materials in the final product must be from approved sources.
- If the materials are blended after manufacture, as opposed to the slag being interground with portland cement clinker during the manufacturing process, the request must state that fact and indicate the blending location.
- The material must meet the requirements of AASHTO M 240.

Reporting requirements for Type I(SM) cement are the same as for Type I cement. However, the testing requirements are as outlined in AASHTO M 240. All mill test reports must clearly indicate the percentage of intermixed slag.

The SCDOT reserves the right to require additional documentation as needed to determine the suitability of a supplier for inclusion. Additionally, the SCDOT may, at any time, remove a supplier from the qualified listing or require additional testing or documentation if confidence in the conformance or suitability of the supplied product is lost.