

SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION  
 QUALIFIED MANUFACTURERS OF CORRUGATED POLYETHYLENE PIPE

Following is a list of Polyethylene Pipe manufacturers qualified to furnish Types "C", "CP", "S", and "SP" pipe meeting the requirements of AASHTO M-252 and AASHTO M-294.

MANUFACTURER/ FACILITY	FILL HEIGHT TABLES RECEIVED	QUALIFIED SIZES OF AASHTO M252 PIPE	QUALIFIED SIZES OF AASHTO M294 PIPE	QUALIFIED SEALANT BRAND(S)	NTPEP PLANT AUDIT STATUS
ADS/Hancor 4640 Trueman Blvd. Hilliard, OH 43026 (614) 658-0050 FAX: (614) 658-0203  Perry, Georgia  Bessemer City, NC  Mebane, NC  Yoakum, TX	Yes	4" – Type C, CP, S, SP 6" – Type C, CP, S, SP 8" – Type C, CP, S, SP 10" – Type C, CP, S, SP	12" – Type S, SP 15" – Type S, SP 18" – Type S, SP 24" – Type S, SP 30" – Type S, SP 36" – Type S, SP 42" – Type S, SP 48" – Type S, SP 54" – Type S 60" – Type S, SP	Vertex, Inc. in Mogadore, OH (Tested to 13 psi) Hamilton Kent in Winchester, TN (Tested to 13 psi) Press Seal Press Seal in Ft. Wayne, IN (Tested to 13 psi) Trelleborg (Tested to 13 psi)	Compliant  Compliant  Compliant  Compliant
Quality Culvert, Inc. 25726 CR 561 PO Box 435 Astatula, FL 34705-0435 (866)343-8488 FAX: (352)343-8422 Attn: Carl Tyner  Astatula, FL  Athens, AL	Yes	8" – Type S, SP 10" – Type S, SP	12" – Type S 15" – Type S 18" – Type S 24" – Type S 30" – Type S 36" – Type S 42" – Type S 48" – Type S	Hamilton Kent in Ontario, Canada (Tested to 10.8 psi)	Compliant  Compliant

SCDOT Contact Person:

G. Michael Lockman, P.E.  
 SCDOT Office of Materials and Research  
 PO Box 191  
 Columbia, SC 29202  
 Telephone: (803) 737-6692  
 FAX: (803) 737-6649

**SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION  
QUALIFIED MANUFACTURERS OF CORRUGATED POLYETHYLENE PIPE**

<p>LANE Enterprises, Inc. 34 Strohm Road Shippensburg, PA 17257 (717) 532-5959 FAX (717) 532-7997 Attn: Mark Dick  Shippensburg, PA</p>	<p align="center">Yes</p>	<p>4" – Type C, CP 6" – Type C, CP, S, SP 8" – Type C, CP, S, SP 10" – Type C, CP, S, SP</p>	<p>12" – Type S, SP 15" – Type S, SP 18" – Type S, SP 24" – Type S, SP 30" – Type S, SP 36" – Type S, SP 42" – Type S, SP 48" – Type S, SP</p>	<p>Hamilton Kent in Ontario, Canada (Tested to 13 psi)</p>	<p align="center">Compliant</p>
<p>Southeast Culvert, Inc. 1094 Bankhead Highway Winder, GA 30680 (770)963-5041 Fax: (770)339-0240  Winder, GA</p>	<p align="center">Yes</p>	<p>8" – Type S, SP 10" – Type S, SP</p>	<p>12" – Type S, SP 15" – Type S, SP 18" – Type S, SP 24" – Type S, SP 30" – Type S, SP 36" – Type S, SP 42" – Type S, SP 48" – Type S, SP 60" – Type S, SP</p>	<p>Vertex, Inc. in Mogadore, OH (12, 15, 18, 24, 30, 36, 48 and 60 inch sizes tested to 13 psi with single gasket. 42, inch size requires double gasket for 13 psi)</p>	<p align="center">Compliant</p>
<p>Blue Diamond Industries, LLC 3399 Tates Creek Road, Suite 110 Lexington, KY 40502 (859)224-0415 Fax: (859)224-0543  Roseboro, NC</p>	<p align="center">Yes</p>	<p>3" – Type C, CP 4" – Type C, CP, S, SP 6" – Type C, CP, S, SP 8" – Type C 10" – Type C</p>			<p align="center">Compliant</p>

SCDOT Contact Person:

G. Michael Lockman, P.E.  
SCDOT Office of Materials and Research  
PO Box 191  
Columbia, SC 29202  
Telephone: (803) 737-6692  
FAX: (803) 737-6649

**SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION  
QUALIFIED MANUFACTURERS OF CORRUGATED POLYETHYLENE PIPE**

<p>Crumpler Plastic Pipe PO Box 2068 Roseboro, NC 28382-2068 1-800-334-5071 FAX: (910)525-5801  Roseboro, NC</p>	<p>Yes</p>	<p>3" – Type C, CP 4" – Type C, CP, S, SP 5" – Type C, CP 6" Type C, CP, S, SP 7" – Type C, CP 8" – Type C, CP, S, SP 9" – Type C, CP 10" – Type C, CP, S, SP</p>	<p>12" – Type S 15" – Type S 18" – Type S 24" – Type S 30" – Type S 36" – Type S 42" – Type S 48" – Type S</p>	<p>Springseal, Inc. (Tested to 13 psi)</p>	<p>Compliant</p>
--	------------	---	--	--	------------------

NOTE: For the following counties: Berkeley, Beaufort, Charleston, Colleton, Dorchester, Georgetown, Horry, and Jasper, provide pipe that is listed with a joint test to 13 psi. For all other counties, use 10 psi minimum unless noted otherwise in the plans or special provisions.

SCDOT Contact Person:

G. Michael Lockman, P.E.  
 SCDOT Office of Materials and Research  
 PO Box 191  
 Columbia, SC 29202  
 Telephone: (803) 737-6692  
 FAX: (803) 737-6649